# J. K. SHAH & CO.

HPLC · SMB · Osmometry



## **Euroline**



# Eurospher I – the HPLC columns for every day

Eurospher I is a silica-based HPLC packing material for a wide range of analytical, semi-preparative and process scale separations. It is ideally suited for high resolution normal phase and reversed phase chromatography. With more than 20 years on the market, the Eurospher stationary phase has earned a reputation as a stable and reliable partner for daily separation tasks.

Eurospher I silica features an outstanding mechanical stability, a high available surface area and a narrow particle size distribution. These properties give Eurospher a long lifetime and high loading capacity.

Available in many different modifications and column sizes, Eurospher I columns adapt easily to your application and truly strike a balance between efficiency, price and performance.

Physical properties of Eurospher I stationary phase:

Silica gel: 2<sup>nd</sup> generation

Particle size: 3 μm, 5 μm, 10 μm, 15 μm

Particle shape: spherical Pore size: 100 Å Specific surface: 350 m²/g Pore volume: 0.9 ml/g

## Column hardware

We design and manufacture HPLC vertex plus column hardware ranging from 2 mm ID to 62 mm ID under strict quality control. A special treated inner surface ensures consistent column packing and high column stability. A wide range of column lengths from 5 mm up to 300 mm are available. The easily exchangeable integrated precolumn for analytical columns is available upon request.

## **HPLC** · **SMB** · Osmometry

#### Modifications

The Eurospher I stationary phase is available in 7 different surface modifications for a wide range of applications, including reversed phase and normal phase applications. Every Eurospher I modification offers high chemical stability and loading capacity. Our long experience and knowledge in producing HPLC columns ensures you of the highest reproducibility. Every modification must pass extensive quality control procedures, guaranteeing the best batch to batch reproducibility.

Modification	USP code	% carbon	pH range
C18	L1	16% (~ 50% endcapping)	2-8
C8	L7	10% (~ 50% endcapping)	2-8
C4	L26	7 % (~ 50 % endcapping)	2-8
NH <sub>2</sub>	L8	4 % (no endcapping)	2-8
CN	L10	7% (no endcapping)	2-8
Diol	L20	5 % (no endcapping)	2-8
Si	L3	0 % (no endcapping)	2-8

### **Applications**

The choice of the appropriate column for a particular application can be a challenging task. With a range of bonded phases offering different selectivity, the Eurospher I family includes columns to meet most separation needs. The table below will help you to choose the best Eurospher I column for a particular application.

Phase type	non polar	polar	acidic	basic	chelator	hydroph. retentlon	shape selectivity
C18	++	++	++	+	++	+	+
C8	++	0	++	+	++	+	+
C4	++	-	0	+	++	0	-
NH <sub>2</sub>	++	+	o	0	++	-	-
CN	++	+	0	0	++	-	-
Diol	++	+	o	-	++	-	-
SI	++	+	-	-	o	-	-




For extreme aqueous applications, we recommend our Eurospher II C18 A material. If you need columns for LC-MS applications, we recommend our Eurospher II column family.



## Separation of sulfa drugs

#### 1 sulfadiazine 1000 sulfamethiazole 3 sulfymethoxypyridazine 900 4 sulfamethoxázóle 800 5 sulfadimethoxine 700 600 500 400 ШAU 300 200 100 Ö 2 6 8 10 12 14 16 18 20 Minutes

## Separation of steroids



Eurospher 100-3 C18 150 x 3.0 mm Column:

A: 0.2 g NaH<sub>2</sub>PO<sub>4</sub> in 1 l H<sub>2</sub>O (pH 4 with H<sub>3</sub>PO<sub>4</sub>) B: ACN Mobile phase:

Gradient: 10% B to 50% B in 20 min

0.5 ml/min Flow rate: Temperature: 40 °C Detection: UV, 240 nm


Eurospher 100-3 C18 150 x 3.0 mm A:  $\rm H_2O$  B: MeOH Column:

Mobile phase:

50% B to 95% B in 19.70 min 0.6 ml/min Gradient:

Flow rate: Temperature: 40 °C UV, 240 nm Detection:

### Separation of steviol glycosides



Eurospher 100-3  $\rm NH_2$  150 x 3.0 mm ACN/ $\rm H_2O$  80 : 20 (v/v), isocratic Column: Mobile phase:

Flow rate: 1 ml/min Temperature: 35 ℃ Detection: UV, 210 nm



## **HPLC** · **SMB** · Osmometry



Modification type	Application areas	Separation mechanism
C18	for acidic, basic and neutral analytes in reversed phase mode (e.g., sulphonamides; anabolic steroids; anti- psychotics; beta blockers; sudan dyes; phenols, preservatives, etc.)	hydrophobic interaction
C8	similar selectivity to C18 phase but less retention due to the lower hydrophobicity; useful for determination of water soluble vitamins, steroids, catecholamines, sedatives, etc.	reduced hydrophobic interaction compared to C18 phase
C4	universal column for different application areas, can also be used in HIC mode (hydrophobic interaction chromatography)	hydrophobic and hydro- philic interaction
CN	for a wide range of applications in normal pase mode as well as reversed phase mode (e.g., steroids, carbo- hydrates, polar compounds)	hydrophobic and hydro- philic interaction
Diol	alternative to the silica packing with shorter equilibra- tion time and comparable selectivity; due to the lower activity of these columns, they can be also used for SEC (size exclusion chromatography) applications	hydrophilic interaction
NH <sub>2</sub>	most flexible phase in the Eurospher II family, can be used in three modes: normal phase, reversed phase and ion chromatography mode (weak anion exchanger); different selectivity to the silica packing; in reversed phase mode mainly used for analysis of carbohydrates	hydrophilic and ionic interaction
Si	wide range of different applications, e.g., SEC but also for normal phase HPLC, good choice for analytical and preparative scale separation of polar compounds	hydrophilic interaction

## Ordering information

► The last 7 digits of the Order No. comprise the stationary phase.

Eurospher I	3 µm	5 μm	10 μm	15 µm
C18	E181ESG	E181ESJ	E181ESN	E181ESQ
C8	E081ESG	E081ESJ	E081ESN	E081ESQ
C4	E041ESG	E041ESJ	E041ESN	E041ESQ
NH <sub>2</sub>	E190ESG	E190ESJ	E190ESN	E190ESQ
CN	E200ESG	E200ESJ	E200ESN	E200ESQ
Diol	E410ESG	E410ESJ	E410ESN	E410ESQ
Si	E000ESG	E000ESJ	E000ESN	E000ESQ

► The first 3 digits of the Order No. comprise the column dimensions.

Analytical columns	2 mm ID	4 mm ID	4.6 mm ID	8 mm ID
5 mm (precolumn)	P5B	P5D	P5D*	n.a.
30 mm length	03B	03D	03E	03G
50 mm length	05B	05D	05E	n.a.
100 mm length	10B	10D	10E	n.a.
125 mm length	12B	12D	12E	n.a.
150 mm length	15B	15D	15E	n.a.
250 mm length	25B	25D	25E	25G
300 mm length	n.a.	30D	n.a.	30G

3 mm ID columns upon request.

All analytical column types from 2 mm ID up to 4.6 mm ID are available with integrated precolumn. Preparative columns are available in the range of 16 mm ID up to 62 mm ID.

\*identical to 4 mm precolumn

Technical data are subject to change without notice.

# **Exclusive Stockiest for India**



## J. K. SHAH & COMPANY

SALES OFFICE:

140/142, PRINCESS STREET, GOVIND BLDG, 3<sup>RD</sup> FLOOR, ROOM NO. 36, MUMBAI-400002

INDIA

VAT TIN: 27640122980 V

TEL: + 91-022-66375415, 22082997

FAX: +91-022-22082997

Mobile: +91-9892933169/7738122935

E-MAIL: jkchemi@gmail.com

URL: www.jklab.in

CST TIN: 27640122980 C